



NOTES:

REMOVE & REPLACE PAVEMENT (SEE NOTE 6)

1. SAW CUT FULL DEPTH THROUGH BITUMINOUS AND CONCRETE PAVEMENT SQUARE (DIAMOND-SHAPED RELATIVE TO THE ROADWAY) A MINIMUM OF 4' FROM CENTER FOR MANHOLES AND A MINIMUM OF 3' FROM CENTER FOR GATE VALVES.
2. THESE REMOVAL DIMENSIONS SHALL MINIMALLY ALLOW FOR VIBRATORY PLATE COMPACTION TO OPERATE PROPERLY.
3. ADJUST ALL SIDES OF STRUCTURES 1/2" LOWER THAN ADJACENT FINAL GRADE, MATCHING STREET GRADES AND CROSS-SLOPES.
4. UTILIZE 1/2"-THICK PUCKS ON GATE VALVES AND 1/2"-THICK CIRCULAR PLATES ON MANHOLES FOR ALL PAVING OF STREETS, DRIVEWAYS, PATHS AND PARKING AREAS.
5. CLEAN ALL LIDS OF ALL GRAVEL, BITUMINOUS OR CONCRETE DURING PAVING OPERATIONS WHILE BITUMINOUS IS HOT AND/OR CONCRETE IS PLASTIC.
6. ANY SAW CUT CLOSER THAN 2' TO THE EDGE OF THE GUTTER SHALL BE EXTENDED TO THE EDGE OF THE GUTTER AND THAT ADDITIONAL PAVEMENT REMOVED AND REPLACED, AS DIRECTED BY THE CITY.



STANDARD DETAILS
 STRUCTURE ADJUSTMENT
 PATCH (BITUMINOUS OR
 CONCRETE)

COTTAGE GROVE, MINNESOTA

LAST REVISION:
 JAN 2014

PLATE NO.
 STR-26